

RAM Commercial Series

LULA ELEVATOR

LIMITED USE LIMITED APPLICATION

LULA





RAM LULA FEATURES

With the same features as a full sized passenger elevator, the RAM LULA is an excellent choice for your low-rise application..

- 30 Feet per minute Travel
- 1400 lb Capacity.
- Automatic Operation.
- 2 Part Interior Cab Sliding Door .
- 2 Part Fire rated Sliding Landing Doors.
- Fire Rated Interior Finish with Stainless Steel Trim.
- Non-skid fire rated flooring.
- Ceiling Lights with Timed On/Off feature.
- Lighted Hall Call Push Buttons.
- Variable Speed Control
- Interior Buttons on Stainless Steel Panel with keyed lockout.
- Over Speed Governor.
- Emergency Alarm & Light.
- Telephone.
- Exterior Manual Raising & Lowering Device.

WHAT IS A LULA ELEVATOR?

The LULA (limited use/limited application) elevator provides vertical transportation for low-rise buildings when a full sized passenger elevator is not practical. LULA elevators can also service areas when vertical platform lifts are not suitable.

LULA elevators are designed to be used in existing or new buildings. Building owners can save a substantial amount over a traditional passenger elevators. The LULA elevator is fully automatic in operation and has a similar look and feel of the larger commercial elevators.

The low foot print requirements makes it ideal for Clubs, Churches, Multi-Family Homes and Schools. Most commercial low rise buildings are excellent candidates for a LULA elevator. You require approximately 30 square feet available for a hoist way, not much larger than an average closet. The finished cab size is 18 square feet maximum.

LULA elevator advantages include lower overhead clearance at the upper landing, shallower pit depths and the ability to operate on single phase power.

LULA elevators are required to be designed, manufactured and installed in accordance with ASME A17.1 /B44 code standards.



Additional options are available. RAM can customize your LULA Elevator to exacting specifications.



WWW.TRUSTRAM.COM



RAM LULA Product Specifications

- **Model - RAM CRL1400.**
- **Rated Load - 1400 lb (635 kg) capacity.**
- **Rated Speed - 30 FPM (0.15m/s).**
- **Travel - Max 25 ft. (7.6m)**
- **Car Dimensions - 43" (1092mm) x 60" (1524) 18 sqft (1.67 sq m) Max.**
- **Car Finish - Laminate wall panels with stainless steel trim.**
- **Car Doors - 2 Part Auto-Sliding Elevator Doors - Stainless.**
- **Landing Doors - 2 Part Auto-Sliding Fire Rated Elevator Doors - Stainless.**
- **Interlocks - Maintains door in a closed and locked position when lift is not at landing.**
- **Levels Served - As required to a maximum of 25 ft.**
- **Number of Car Openings - 3 Maximum.**
- **Operation - Automatic Operation as per code.**
- **Key Operated - Illuminated Keyed Call Station.**
- **Power Supply - 220v/1Ph/60Hz 20A Breaker.**
- **Lighting Supply - 110v/1Ph/15A.**



WWW.TRUSTRAM.COM



RAM LULA Product Specifications

Guide Rails

- Rigid guide rail system requires no backing plates or structural supports in the hoist way walls.

Drive System

- Traction sheave driven by 1.5 HP AC Motor.
- Manual lowering and raising capability.
- 220V/110V Single Phase Power Supply
- Drive system integrated with structural guide rail framework requires no machine room, and is located at top of shaft on guide rail system.

Options

- Glass Cab with Stainless trim
- Custom Stainless Handrails
- Stainless Kick plates on Cab Walls.
- Custom Cab Size
- Full DC Backup



WWW.TRUSTRAM.COM